



Henan Huaxing Wires and Cable Co.,Ltd
Yong'an Industry Zone, Gongyi, Henan, China 450012
Website: www.huaxingcable.com
E-mail: huaxing@huaxingcable.com
Tel: 0086 371 8662 7929
Fax: 0086 371 64108619

Quadruplex Service Drop Wire

编码名称 Code word	AWG or kcmil	Bare Neutral Messenger		Phase Conductor Code word		重量 Weight (kg/km)
		AAC 根数和单丝直径 Stranding and Wires Dia. (mm)	额定抗 拉强度 Rated strength (lbs)	AAC 根数和单丝直径 Stranding and Wires Dia. (mm)	绝缘厚度 insul. Thick. (mm)	
Clydesdale	3*4AWG+1*4AWG	7/1.96	881	1/5.19	1.14	299
Pinto	3*4AWG+1*4AWG	7/1.96	881	7/1.96	1.14	306
Mustang	3*2AWG+1*2AWG	7/2.47	1350	7/2.47	1.14	461
Criollo	3*1/0AWG+1*1/0AWG	7/3.12	1990	19/1.89	1.52	744
Percheron	3*2/0AWG+1*2/0AWG	7/3.50	2510	19/2.13	1.52	914
Hanoverian	3*3/0AWG+1*3/0AWG	19/2.39	3310	19/2.39	1.52	1127
Oldenburg	3*4/0AWG+1*4/0AWG	19/3.25	4020	19/3.25	1.52	1995
Lippizaner	3*336.4+1*336.4	19/3.38	6146	19/3.38	2.03	2236

编码名称 Code word	AWG or kcmil	Bare Neutral Messenger			Phase Conductor Code word		重量 Weight (kg/km)
		ACSR 根数和单丝直径 Stranding and Wires Dia. (mm)		额定抗 拉强度 Rated strength (lbs)	AAC	绝缘厚度 insul. Thick. (mm)	
		ST	AL		根数和单丝直径 Stranding and Wires Dia. (mm)		
Morochuca	3*6AWG+1*6AWG	1/1.68	6/1.68	1190	1/4.11	1.14	221
Chola	3*6AWG+1*6AWG	1/1.68	6/1.68	1190	7/1.56	1.14	227
Morgan	3*4AWG+1*4AWG	1/2.12	6/2.12	1860	1/5.19	1.14	331
Hackney	3*4AWG+1*4AWG	1/2.12	6/2.12	1860	7/1.96	1.14	338
Palomino	3*2AWG+1*2AWG	1/2.67	6/2.67	2850	7/2.47	1.14	511
Costena	3*1/0AWG+1*1/0AWG	1/3.37	6/3.37	4380	19/1.89	1.52	824
Grullo	3*2/0AWG+1*2/0AWG	1/3.78	6/3.78	5310	19/2.13	1.52	1015
Suffolk	3*3/0AWG+1*3/0AWG	1/4.25	6/4.25	6620	19/2.39	1.52	1254
Appaloosa	3*4/0AWG+1*4/0AWG	1/4.77	6/4.77	8350	19/2.68	1.52	1554
Bronco	3*336.4+1*336.4	1/3.47	6/3.47	8680	19/3.38	2.03	2321
Gelding	3*336.4+1*4/0AWG	1/4.77	6/4.77	8350	19/3.38	2.03	2221



Henan Huaxing Wires and Cable Co.,Ltd
Yong'an Industry Zone, Gongyi, Henan, China 450012
Website: www.huaxingcable.com
E-mail: huaxing@huaxingcable.com
Tel: 0086 371 8662 7929
Fax: 0086 371 64108619

编码名称 Code word	AWG or kemil	裸承载线 Bare Neutral Messenger		中线 Phase Conductor Code word		重量 Weight (kg/km)
		AL-ALLOY 根数和单丝直径 Stranding and wires Dia. (mm)	额定抗 拉强度 Rated strength (lbs)	AAC 根数和单丝直径 Stranding and wires Dia. (mm)	绝缘厚度 insul. Thick. (mm)	
Bay	3*6AWG+1*30.58	7/1.68	1110	1/4.11	1.14	207
French Coach	3*6AWG+1*30.58	7/1.68	1110	7/1.56	1.14	213
German Coach	3*4AWG+1*48.69	7/2.12	1760	1/5.19	1.14	309
Arabian	3*4AWG+1*48.69	7/2.12	1760	7/1.96	1.14	316
Belgian	3*2AWG+1*77.47	7/2.67	2800	7/2.47	1.14	476
Shetland	3*1/0AWG+1*123.3	7/3.37	4460	19/1.89	1.52	768
Thoroughbred	3*2/0AWG+1*155.4	7/3.78	5390	19/2.13	1.52	945
Trotter	3*2/0AWG+1*195.7	7/4.25	6790	19/2.39	1.52	1166
Walking	3*4/0AWG+1*246.9	7/4.77	8560	19/2.68	1.52	1442